

# FIXING INSTRUCTIONS



## KINGFISHER FRAMED LOUVRE PANEL

- The framed louvre panel is to be installed in pre-prepared openings. Where the louvre panel is to be installed into a cladding system then the dedicated openings must be sealed/weathered prior to installing the louvre panel.
- Apply suitable silicone sealant (supplied by others) round the perimeter of the back of the flange and insert the louvre panel into the opening.
- The louvre panel should be mechanically fixed to the structure through the external flange (fixings supplied by others).
  - Drill appropriate sized holes in the perimeter of the flange to suit the fixings being used. Fixing should be a minimum 50mm from corners and maximum of 300mm centres.
  - Ensure holes are positioned such that the fixings will not be too close to the edge.
  - When drilling the fixing holes, care must be taken not to damage the surrounding surface of the aluminium or any coating.

FOR FURTHER INFORMATION ON ALL KINGFISHER PRODUCTS PLEASE CONTACT:

.....

KINGFISHER LOUVRE SYSTEMS

Brookhill Industrial Estate, Plymouth Avenue, Pinxton, Nottingham, NG16 6NS  
Telephone: (+44) 01773 814102 Web: [www.kingfisherlouvres.com](http://www.kingfisherlouvres.com)  
Email: [admin@kingfisherlouvres.com](mailto:admin@kingfisherlouvres.com)

