

FIXING INSTRUCTIONS



KINGFISHER GLAZING FRAMES

- Kingfisher glazing frames are supplied as fully assembled units designed to be installed within pre-prepared rebates on site by others.
- The glazing depth should be specified at point of order; typically, standard sizes are 24mm or 28mm. For other depths please contact Kingfisher’s Technical Sales team who can advise.
- The rebates for installation can vary but typically would be a minimum of 20mm. The leg of the glazing louvre is typically either 38mm or 41mm.
- The louvre must be held within the rebate using a suitable glazing material (supplied by others) to provide a weatherproof seal to the edge of the frame and into the glazing rebate.
- If required, once within the glazing rebate, further sealant can be used at the face or rear of the louvre to finish the edges where the product sits within the rebate.
- No mechanical fixings are supplied with the glazing frames and so the glazing compound must be suitable to fix the weight of the louvres supplied. Weights available on request.

If further assistance is required with installation, we can provide details of preferred distributors who can offer costs for their installation services.

FOR FURTHER INFORMATION ON ALL KINGFISHER PRODUCTS PLEASE CONTACT:

.....

KINGFISHER LOUVRE SYSTEMS

Brookhill Industrial Estate, Plymouth Avenue, Pinxton, Nottingham, NG16 6NS
Telephone: (+44) 01773 814102 Web: www.kingfisherlouvres.com
Email: admin@kingfisherlouvres.com

