

Specification Clause

Louvred Doors

Provide louvre door sets to as shown on drawings reference Doors and frames to be extruded aluminium grade 6063 T6 to BS 1474. Leaf to be outward opening*.

Ironmongery, standard doors: Euro profile cylinder lock in Euro profile deadlock case, surface mounted Chubb door bolt to slave leaf, aluminium D handle powder coated to match door, dictator gas spring to assist opening and hold door open at 90°/fully closed.

*Ironmongery, fire escape doors: aluminium D handle powder coated to match door, door stay with pull cord release, Briton panic push pad (single doors)/horizontal panic bar with 3-point locking (double doors). *

Louvre blade type:

KC120/KW50Z/KW75Z/KW100Z/KW75S/KW75HPG/KW100D/(KW75/100T)/KW100/100T* with sprung metal blade clips, blade centres: mm.

Finish: polyester powder coating to BS 6496/PVF2/anodised AA25 to BS 3987/natural mill finish*, colour:

Accessories: HDPE/aluminium* bird guard/insect guard*, special ironmongery:

Delete as applicable

Louvres to be supplied by:

Kingfisher Louvre Systems Ltd,
Plymouth Avenue
Brookhill Industrial Estate
Pinxton
Nottingham
NG16 6NS

Tel: 01773 814 102

admin@kingfisherlouvres.com